

0.1 Liter Turkish delight and chocolate tin box HF

HF

Technical Specifications

Mold Code	HF
Diameter	60
Length	95
Height	22
Volume	0.1 lt

Applicable Features

Kalınlık

0,22 mm · 0,24 mm · 0,25 mm

İç Kaplama

Silverlaklı · Gold Laklı · Puntalık Laklı · Çift Laklı · Pigment Laklı · Pigment Lak+Laklı · Çift Pigment Laklı · Krem Emaye Laklı · Bej Laklı · Şeffaf Laklı · Krem Laklı · Dekoratif Gold Laklı · Gri Laklı · Yok

Dış Kaplama

Silverlaklı · Gold Laklı · Emaye · Çift Laklı · Ofset Baskılı · Şeffaf Laklı · Dekoratif Gold Laklı · Yok

Delik

Yok

Kapak

Geçme Kapak

Kulp / Menteşe

Yok

39

Yok

Dikiş/Kenet

Yok

Dikiş Kaplama

Yok

Forma / Kordon

Yok

Product Description

0.1 Liter Turkish Delight and Chocolate Tin Box

The 0.1 liter Turkish delight and chocolate tin box HF is a compact metal food package designed for Turkish delight, chocolate, dragees, and small confectionery portions. For the HF mold, the technical sheet lists a 60 mm diameter, 95 mm length, 22 mm mold height, and 0.1 L volume. Its small size is useful for samples, premium single portions, gifts, and promotional packs where space matters. A slip lid provides simple opening and closing. The technical sheet lists the seam / lock-seam field as "None", and this source detail is preserved as written. Manufactured by Kontensan, this model is suitable for Turkish delight tin box, Turkish delight gift box, chocolate tin, chocolate tin box, Turkish chocolate box, and compact branded confectionery packaging projects.

Key Features of the 0.1 Liter Turkish Delight and Chocolate Tin Box

60 × 95 mm Compact Body and 0.1 L Capacity

This product is included in Kontensan's Food Tin & Metal Packaging main category and the Turkish Delight, Chocolate and Dragee Tin Boxes subcategory. The 60 × 95 mm body and 22 mm height give the tin a compact format. The 0.1 L capacity supports low-volume Turkish delight present, Turkish delight gift box, chocolate tin, sample, and promotional packaging projects.

Slip Lid and No Seam / Lock-Seam Construction

The HF tin box uses a slip lid. The technical sheet lists the seam / lock-seam field as "None", and no seam coating is applied. The product has no hole, handle, hinge, or decorative bead. Available metal thickness options are 0.22 mm, 0.24 mm, and 0.25 mm. This structure gives the package a simple and lightweight base for branded serial-production projects.

Offset Printing and Coating Options

The inner surface can be produced with silver lacquer, gold lacquer, spot lacquer, double lacquer, pigment lacquer, pigment lacquer + lacquer, double pigment lacquer, cream enamel lacquer, beige lacquer, clear lacquer, cream lacquer, decorative gold lacquer, or grey lacquer. The outer surface can use silver lacquer, gold lacquer, enamel, double lacquer, offset printing, clear lacquer, or decorative gold lacquer. These options support branded Turkish delight chocolate box, Turkish candy box, and chocolate tin projects.

Applications and Brand Value

The 0.1 liter Turkish delight and chocolate tin box can be used for small portions of Turkish delight, chocolate, dragees, confectionery, samples, and promotional products. Its compact size is practical for gift sets and retail points with limited shelf space. The metal surface supports offset printing and clear brand communication even on a small package. Kontensan combines coating and printing options with serial production capability, making this tin box suitable for retail, export, corporate gift, and campaign projects.

Frequently Asked Questions - FAQ

What are the dimensions of the 0.1 liter tin box?

The HF technical sheet lists a 60 mm diameter, 95 mm length, and 22 mm mold height. The alternative 0.1 L sample product is also listed with an actual product height of 22 mm.

What is the capacity of this tin box?

The technical sheet states a 0.1 L volume for the HF model.

Is this tin box lock-seamed?

No. The technical sheet lists the seam / lock-seam field as "None".

Can this chocolate tin box be offset printed?

Yes. Offset printing is listed among the available outer coating options in the technical sheet.