

1 Liter Turkish delight and chocolate tin box JH

JH

Technical Specifications

Mold Code	JH
Diameter	80
Length	120
Height	120
Volume	1 - 2 lt

Applicable Features

Kalınlık

0,24 mm · 0,25 mm

İç Kaplama

Silverlaklı · Gold Laklı · Puntalık Laklı · Çift Laklı · Pigment Laklı · Pigment Lak+Laklı · Çift Pigment Laklı · Krem Emaye Laklı · Bej Laklı · Şeffaf Laklı · Krem Laklı · Dekoratif Gold Laklı · Gri Laklı · Yok

Dış Kaplama

Silverlaklı · Gold Laklı · Emaye · Çift Laklı · Ofset Baskılı · Şeffaf Laklı · Dekoratif Gold Laklı · Yok

Delik

Yok

Kapak

Geçme Kapak

Kulp / Menteşe

Menteşeli

39

Yok

Dikiş/Kenet

Kenetli

Dikiş Kaplama

Yok

Forma / Kordon

Yok

Product Description

1 Liter Turkish Delight and Chocolate Tin Box

The 1 liter Turkish delight and chocolate tin box JH is a metal food package designed to protect, transport, and present Turkish delight, chocolate, dragees, confectionery, and regional specialties. For the JH mold, the technical sheet lists an 80 mm diameter, 120 mm length, 120 mm mold height, and an applicable volume range of 1–2 liters. Its slim and tall shape creates a different shelf silhouette compared with wider tins. The slip lid and hinged structure work together, keeping the lid connected to the body during repeated use. The lock-seamed body supports clean serial production. Manufactured by Kontensan, this model is suitable for Turkish delight tin box, Turkish delight gift box, chocolate tin, chocolate tin box, Turkish chocolate box, and branded confectionery packaging projects.

Key Features of the 1 Liter Turkish Delight and Chocolate Tin Box

80 × 120 mm Body and 1–2 L Capacity Range

This product is included in Kontensan's Food Tin & Metal Packaging main category and the Turkish Delight, Chocolate and Dragee Tin Boxes subcategory. The 80 × 120 mm base and 120 mm height give the tin box a slim vertical form. The 1–2 L applicable volume range supports different filling quantities for Turkish delight present, Turkish delight gift box, chocolate tin, and export packaging projects.

Hinged Slip Lid and Lock-Seamed Body

The JH tin box uses a slip lid with a hinged structure. The body construction is lock-seamed, and the technical sheet states that no seam coating is applied. The product has no hole or decorative bead. Available metal thickness options are 0.24 mm and 0.25 mm. This structure combines repeat-use convenience with a clean base for serial production.

Offset Printing and Coating Options

The inner surface can be produced with silver lacquer, gold lacquer, spot lacquer, double lacquer, pigment lacquer, pigment lacquer + lacquer, double pigment lacquer, cream enamel lacquer, beige lacquer, clear lacquer, cream lacquer, decorative gold lacquer, or grey lacquer. The outer surface can use silver lacquer, gold lacquer, enamel, double lacquer, offset printing, clear lacquer, or decorative gold lacquer. These options support branded Turkish delight chocolate box, Turkish candy box, and chocolate tin projects.

Applications and Brand Value

The 1 liter Turkish delight and chocolate tin box can be used for Turkish delight, chocolate, dragees, confectionery, and regional food products. Its slim and tall body creates a distinctive shelf appearance, while the hinged lid supports repeat use. The metal surface provides a strong area for offset printing and brand communication. Kontensan combines coating and printing options with serial production capability, making this tin box suitable for retail, export, corporate gift, and wholesale projects.

Frequently Asked Questions - FAQ

What are the dimensions of the 1 liter tin box?

The JH technical sheet lists an 80 mm diameter, 120 mm length, and 120 mm mold height. The alternative 1 L sample product is also listed with an actual product height of 120 mm.

What volume range is available for this tin box?

The technical sheet states an applicable volume range of 1–2 liters for the JH mold.

Is this tin box hinged?

Yes. The technical sheet lists a slip lid and identifies the handle / hinge field as hinged.

Is this tin box lock-seamed?

Yes. The technical sheet identifies the body construction as lock-seamed and states that no seam coating is used.